

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
24930	PECK LEDGE LIGHT	41 04 38 N 73 22 11 W	FI G 2.5s	61	7	White conical tower, middle part brown, on black cylindrical pier.	
			*				45/01
CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
395	North Chesapeake Entrance Lighted Bell Buoy NCC	36 57 36 N 75 52 59 W	FI Y 4s		7	Yellow.	
		*			*		45/01
1575	Fourteen Foot Bank Light	39 02 54 N 75 11 56 W	FI W 9s (R sector) 3s fl 6s ec. 2s fl 2s ec. 2s fl 14s ec.	59	W 13 R 10	White tower and dwelling on black cylindrical pier.	Red from 332°.5 to 151°, covers Brown and Joe Flogger Shoals. HORN: 1 blast ev 30s (3s bl). Maintained from Mar. 15 to Dec. 15.
			*				45/01
2140	- Channel Buoy 16						Remove from list.
							*
							45/01
2420	LEIPSI RIVER LIGHT 2		FI R 4s	23	3	TR on skeleton tower.	
					*	*	45/01
	Buoys located 50 feet outside channel limit.						
2895	DEEPWATER RANGE FRONT LIGHT	39 40 46 N 75 31 02 W	Oc G 4s	30		On skeleton tower.	Higher intensity on rangeline. Lighted throughout 24 hours. Passing light visible all around.
		*	*		*		*
							45/01
	*Add Heading: *Naples Bay Channel						
*2897	DEEPWATER RANGE FRONT PASSING LIGHT		Oc R 4s	30	6	On skeleton tower. Same structure as Deepwater Range Front Light.	
							45/01
	*Add Headings: *Delaware River (Main Channel) *Bulkhead Bar Range						
2900	Pennsville Dike Danger Buoy PDA					White with orange bands worded DANGER DIKE. Nun.	Maintained from May 15 to Nov. 1.
							45/01
3415	- RANGE FRONT LIGHT	39 53 20 N 75 11 36 W	Q G	33		On skeleton tower.	Visible on range line only. Lighted throughout 24 hours.
		*					45/01
4540	- Buoy 38					Red nun.	
	*					*	45/01

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2001

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
7040	<i>Cape Henry Wreck Lighted Buoy 2CH 250 yards, 225° from last reported position of wreck. Marks wreck of CHILORE.</i>	36 57 33 N 76 00 46 W	Q R		3	Red.	
					*		45/01
9310	Thimble Shoal Light	37 00 55 N 76 14 23 W	Fl W 10s	55	20	Red conical tower on brown cylindrical pier.	HORN: 1 blast ev 30s (3s bl). Operates continuously.
		*					45/01
17675	Dahlgren Naval Mooring Buoy A						<i>Remove from list.</i>
							* 45/01
	*Add Heading: *Manatee Cove Marina Race Course						
*19687	Buoy 1					Green can.	Private aid.
							45/01

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2001

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2420	- INNER RANGE REAR LIGHT 1,000 yards, 022.4° from front light.		Iso R 6s	57		KRW on skeleton tower on dolphin.	Visible 4° each side of rangeline.
							* 45/01
5415	- RANGE FRONT LIGHT	30 36 28 N 88 01 59 W	Q G	25		KRW on skeleton tower on piles.	For downbound traffic. Visible 2° each side of range line.
		*					45/01
5417	- RANGE FRONT PASSING LIGHT		Q W	27	6	On same structure as Mobile Channel Range Front Light.	
			*		*		45/01
5423	- RANGE REAR PASSING LIGHT		Q W	14	4	On same structure as Mobile Channel Range Rear Light.	
			*	*	*		* 45/01
6290	- LIGHT 17	30 31 24 N 88 05 36 W	Fl G 2.5s	17	3	SG on pile.	Ra ref.
							* 45/01
16215	SOUTHEAST LOUISIANA CANAL ENTRANCE LIGHT 1	29 15 54 N 90 06 18 W	Fl G 2.5s	17	3	SG on platform.	Ra ref.
				*			45/01

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
24145	UPPER PEGGY'S LAKE INBOUND AND CROSSOVER OUTBOUND RF LIGHTS	29 44 26 N 95 03 41 W	Q G	35		KRW on skeleton tower on piles.	Double purpose range light. Visible all around; higher intensity on rangeline.
	*	*				*	* 45/01
29095	- RANGE FRONT LIGHT	29 43 21 N 84 58 48 W	Q G	17		KRW-I on dolphin.	Visible all around; higher intensity on rangeline.
		*		*			45/01
32445	- RANGE C FRONT LIGHT	30 16 00 N 88 11 25 W	Q G	15		KRW-I on dolphin.	Visible 4° each side of rangeline.
							* 45/01
*32447	RANGE C FRONT PASSING LIGHT		Q W	17	6	On same structure as Pass Aux Herons Range Front Light.	
							45/01
32450	- RANGE C REAR LIGHT 2,599 yards, 247.1° from front light.		Iso W 6s	57		KRW-I on piles.	Visible 4° each side of rangeline.
							* 45/01
*32452	-RANGE C REAR PASSING LIGHT		Q W	14	6	On same structure as Pass Aux Herons Range C Rear Light.	
							45/01
*32627	-Daybeacon 33					SG-SY on pile.	Ra ref.
							45/01
*32629	-Daybeacon 34					TR-TY on pile.	Ra ref.
							45/01
32630	- Daybeacon 35					SG-SY on pile.	Ra ref.
	*						45/01
32635	- Daybeacon 36					TR-TY on pile.	Ra ref.
	*						45/01

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
16963	DRIFTWOOD POINT LIGHT	49 12 46 N 94 56 45 W	FI W 6s	35 11	6	NR on skeleton tower.	
		*					45/01

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.